



NOTES:

1. SURFACE LEVELS ALONG BOUNDARIES MUST BE TAKEN FROM INSIDE THE ADJOINING (NEIGHBORING) ALLOTMENTS.
2. RETAINING WALL LEVELS AND HEIGHTS SHOULD BE SPECIFIED AT THE FOLLOWING LOCATIONS:
 - a) AT THE START AND END OF ANY RETAINING WALL
 - b) AT THE INTERSECTION OF TWO OR MORE RETAINING WALLS: 0.3 METERS FROM THE START / END OF EACH RETAINING WALL (AS SHOWN ABOVE).
 - c) AT ALL LOCATION WHERE THE RETAINING WALL IS AT MAXIMUM HEIGHT.
 - d) AT A MAXIMUM SPACING OF 10m ALONG THE LENGTH OF ANY RETAINING WALL
 - e) WHERE A RETAINING WALL TRANSITIONS BETWEEN CUT AND FILL (I.E. RETAINING WALL HEIGHT = 0.00m)

LEGEND

- — — — — = RETAINING WALL
- TRW = TOP OF RETAINING WALL LEVEL
- BRW = BOTTOM OF RETAINING WALL LEVEL
- 0.00m HIGH = APPROX OVERALL RETAINING WALL HEIGHT

STANDARD DETAIL
EXAMPLE RETAINING WALL LAYOUT



CITY OF
Port Adelaide Enfield

File Name

SK1024

Revised	17 NOV 2016
Approved	N.WICKER
Revision	A